

# SSB Battery Screwdriver

1.5 to 12 Nm (1.1 to 8.8 ft.lb) - 360 and 750 rpm

The SSB range has been developed to meet the needs for a high quality cordless screwdriver specifically for the industrial user.

High rundown speeds: **>700rpm** = reduced process time

Excellent torque accuracy assures joint integrity and quality

Extreme durability of components: **>200000 tightening operations** means high duty cycles and productivity as well as lower operating costs

2.6Ah / 12volt NiMh battery packs can give **up to 800 assembly operations per charge**

T handle shape with **2 position battery clip**

Ergonomic design features for improved **operator comfort** and output

**Optical and audible OK** torque indicators and low voltage warning light

Sound level **<70dB(A)** and vibration **<2.5m/s<sup>2</sup>** ref. EN 50260

## Technical features for class-leading durability & efficiency

- Super G high magnetic motor for 30% more power
- Increased reverse torque for efficient fastener removal
- Industrial duty bearings & gearbox components for consistent power delivery and torque repeatability
- All electronic function processors for enhanced durability
- 1/4" hexagon quick release bit holder accepts ISO standard power bits.



## How to order standard screwdriver package

- 1- Specify screwdriver model & part number
- 2- Choose battery type & quantity
- 3- Choose charger suitable for local voltage

Battery not included in standard offering

## SSB060 / SSB120

### OPTIONAL ACCESSORIES

		PART NO.
<b>Battery type</b>		
• Battery NiCd 12V 2.0 Ah - 0.73kg (1.6lb)	BCD 12	615 396 370 0
• Battery NiMh 12V 2.6 Ah - 0.73kg (1.6lb)	BMH 12	615 396 371 0
<b>Battery charger</b>		
• Charger NiCd/NiMh 230V - Europe	CH40 EU	615 396 367 0
• Charger NiCd/NiMh 230V - UK	CH40 UK	615 396 368 0
• Charger NiCd 120V - USA	CH30 US	615 396 425 0

MODEL	PART NUMBER	TORQUE RANGE		ROTATIONAL SPEED	DRIVE	HEIGHT		WEIGHT	
		Nm	ft.lb	rpm	in	mm	in.	kg	lb
SSB060-T750-S4Q	615 165 240 0	1.5-6	1.1-4.4	700-750	Hex. 1/4	250	9.8	1.9	4.3
SSB120-T360-S4Q	615 165 250 0	5.0-12	3.7-8.8	360	Hex. 1/4	250	9.8	1.9	4.3

